

SIZE SPECIFICATIONS:

52" W x 68" H



FRONT VIEW



SIDE VIEW



ISOMETRIC VIEW

PARTS	QTY	QTY
-------	-----	-----

	101	2
	102	1
	103	1
	104	2
	105	4
	106	4
	107	2
	108	1
	109	2

FRAME ASSEMBLY

STEP 1: Assemble Frame

PARTS REQUIRED: 101, 102, 103, 104, 105, 106

- 1. Insert the backrest into the seat.
- 2. Tighten the screws.
- 3. Insert the base into the seat.
- 4. Tighten the screws.
- 5. Insert the casters into the base.
- 6. Tighten the screws.
- 7. Insert the casters into the base.
- 8. Tighten the screws.

STEP 2:

PARTS REQUIRED: 107, 108

- 1. Insert the backrest into the seat.
- 2. Tighten the screws.
- 3. Insert the base into the seat.
- 4. Tighten the screws.
- 5. Insert the casters into the base.
- 6. Tighten the screws.
- 7. Insert the casters into the base.
- 8. Tighten the screws.

STEP 3:

PARTS REQUIRED: 109, 110, 111, 112, 113, 114

- 1. Insert the backrest into the seat.
- 2. Tighten the screws.
- 3. Insert the base into the seat.
- 4. Tighten the screws.
- 5. Insert the casters into the base.
- 6. Tighten the screws.
- 7. Insert the casters into the base.
- 8. Tighten the screws.
- 9. Insert the casters into the base.
- 10. Tighten the screws.

FABRIC INSTALLATION

- 1. Insert the fabric into the seat.
- 2. Tighten the screws.
- 3. Insert the base into the seat.
- 4. Tighten the screws.
- 5. Insert the casters into the base.
- 6. Tighten the screws.
- 7. Insert the casters into the base.
- 8. Tighten the screws.
- 9. Insert the casters into the base.
- 10. Tighten the screws.



The fabric is installed in the seat. The fabric is inserted into the seat. The fabric is inserted into the seat. The fabric is inserted into the seat.

Insert the fabric into the seat.