

### DESCRIPTION:

84" H x 58" W



FRONT VIEW



SIDE VIEW



ISOMETRIC VIEW

| PARTS | CODE | QTY |
|-------|------|-----|
|-------|------|-----|

|  |     |   |
|--|-----|---|
|  | 01  | 2 |
|  | 02  | 1 |
|  | 03  | 4 |
|  | 04  | 4 |
|  | 05  | 4 |
|  | 06  | 4 |
|  | 07  | 4 |
|  | 08  | 4 |
|  | 09  | 4 |
|  | 10  | 4 |
|  | 11  | 4 |
|  | 12  | 4 |
|  | 13  | 4 |
|  | 14  | 4 |
|  | 15  | 4 |
|  | 16  | 4 |
|  | 17  | 4 |
|  | 18  | 4 |
|  | 19  | 4 |
|  | 20  | 4 |
|  | 21  | 4 |
|  | 22  | 4 |
|  | 23  | 4 |
|  | 24  | 4 |
|  | 25  | 4 |
|  | 26  | 4 |
|  | 27  | 4 |
|  | 28  | 4 |
|  | 29  | 4 |
|  | 30  | 4 |
|  | 31  | 4 |
|  | 32  | 4 |
|  | 33  | 4 |
|  | 34  | 4 |
|  | 35  | 4 |
|  | 36  | 4 |
|  | 37  | 4 |
|  | 38  | 4 |
|  | 39  | 4 |
|  | 40  | 4 |
|  | 41  | 4 |
|  | 42  | 4 |
|  | 43  | 4 |
|  | 44  | 4 |
|  | 45  | 4 |
|  | 46  | 4 |
|  | 47  | 4 |
|  | 48  | 4 |
|  | 49  | 4 |
|  | 50  | 4 |
|  | 51  | 4 |
|  | 52  | 4 |
|  | 53  | 4 |
|  | 54  | 4 |
|  | 55  | 4 |
|  | 56  | 4 |
|  | 57  | 4 |
|  | 58  | 4 |
|  | 59  | 4 |
|  | 60  | 4 |
|  | 61  | 4 |
|  | 62  | 4 |
|  | 63  | 4 |
|  | 64  | 4 |
|  | 65  | 4 |
|  | 66  | 4 |
|  | 67  | 4 |
|  | 68  | 4 |
|  | 69  | 4 |
|  | 70  | 4 |
|  | 71  | 4 |
|  | 72  | 4 |
|  | 73  | 4 |
|  | 74  | 4 |
|  | 75  | 4 |
|  | 76  | 4 |
|  | 77  | 4 |
|  | 78  | 4 |
|  | 79  | 4 |
|  | 80  | 4 |
|  | 81  | 4 |
|  | 82  | 4 |
|  | 83  | 4 |
|  | 84  | 4 |
|  | 85  | 4 |
|  | 86  | 4 |
|  | 87  | 4 |
|  | 88  | 4 |
|  | 89  | 4 |
|  | 90  | 4 |
|  | 91  | 4 |
|  | 92  | 4 |
|  | 93  | 4 |
|  | 94  | 4 |
|  | 95  | 4 |
|  | 96  | 4 |
|  | 97  | 4 |
|  | 98  | 4 |
|  | 99  | 4 |
|  | 100 | 4 |

### STEP 1 assembly

#### STEP 1: Assemble backrest

PARTS REQUIRED: 001, 1, 002, 001, 001, 0, 0

- 1. Place the backrest on the floor.
- 2. Insert the backrest support bar.
- 3. Tighten the backrest support bar.
- 4. Connect the backrest support bar to the backrest.
- 5. Connect the backrest support bar to the backrest.
- 6. Connect the backrest support bar to the backrest.
- 7. Connect the backrest support bar to the backrest.
- 8. Connect the backrest support bar to the backrest.
- 9. Connect the backrest support bar to the backrest.
- 10. Connect the backrest support bar to the backrest.

#### STEP 2:


PARTS REQUIRED: 001, 0, 0

- 1. Place the backrest on the floor.
- 2. Insert the backrest support bar.
- 3. Tighten the backrest support bar.
- 4. Connect the backrest support bar to the backrest.
- 5. Connect the backrest support bar to the backrest.
- 6. Connect the backrest support bar to the backrest.
- 7. Connect the backrest support bar to the backrest.
- 8. Connect the backrest support bar to the backrest.
- 9. Connect the backrest support bar to the backrest.
- 10. Connect the backrest support bar to the backrest.

#### STEP 3:

PARTS REQUIRED: 001, 1, 002, 001, 001, 0, 0

- 1. Place the backrest on the floor.
- 2. Insert the backrest support bar.
- 3. Tighten the backrest support bar.
- 4. Connect the backrest support bar to the backrest.
- 5. Connect the backrest support bar to the backrest.
- 6. Connect the backrest support bar to the backrest.
- 7. Connect the backrest support bar to the backrest.
- 8. Connect the backrest support bar to the backrest.
- 9. Connect the backrest support bar to the backrest.
- 10. Connect the backrest support bar to the backrest.



### FABRIC INSTALLATION

- 1. Place the fabric on the chair.
- 2. Insert the fabric into the seat.
- 3. Tighten the fabric.
- 4. Connect the fabric to the chair.
- 5. Connect the fabric to the chair.
- 6. Connect the fabric to the chair.
- 7. Connect the fabric to the chair.
- 8. Connect the fabric to the chair.
- 9. Connect the fabric to the chair.
- 10. Connect the fabric to the chair.



Minimum recommended  
fabric weight:  
Minimum recommended  
fabric weight:  
Minimum recommended  
fabric weight:

Minimum recommended  
fabric weight: